



دوربین مدار بسته

AXIS Q6055-E

درباره ما

شرکت مهندسی مکسا مفتخر است که توانسته است طیف وسیعی از محصولات سخت افزاری مرتبط با حوزه امنیت کنترل تردد مانند انواع دوربین های مدار بسته، انواع دستگاه های حضور و غیاب، گیت های کنترل تردد، راهبندها، گیت ها و راکت های بازرسی بدنی و همچنین محصولات نرم افزاری شامل نرم افزار اکسس کنترل، نرم افزار جامع حراست، نرم افزار پلاک خوان و... را در اختیار کلیه کسب و کارهای بزرگ ایرانی قرار دهد.

چرا مکسارا انتخاب کنیم؟

- ✓ ۱ سال گارانتی محصولات
- ✓ ۵ سال وارانتی محصولات
- ✓ پشتیبانی فعال
- ✓ کارشناس حضوری
- ✓ تعمیر دوره ای
- ✓ تعویض دستگاه
- ✓ نصب تخصصی
- ✓ تیکت پشتیبانی

مشخصات

- ✓ رزولیشن تصویر: ۱۹۲۰x۱۰۸۰p (۱۰۸۰p HDTV)
- ✓ فشرده سازی تصویر: H.264, Zipstream
- ✓ سنسور پردازش تصویر: ۱/۲.۸ اینچی CMOS
- ✓ میدان دید عمودی: ۱.۳-۳۶.۸°
- ✓ میدان دید افقی: ۰۲.۲۳-۶۲.۸°
- ✓ دید در شب و روز: فیلتر برش مادون قرمز با قابلیت جدا سازی خودکار
- ✓ فاصله کانونی: ۴.۴۴-۱۴۲.۶ میلی متر
- ✓ حافظه: ۵۱۲ مگابایت رم و ۲۵۶ مگابایت فلش
- ✓ مقاوم در برابر خرابکاری با برخورداری از گواهی IK1۰
- ✓ زوم اپتیکال ۳۲ برابر
- ✓ وزن: ۳/۷ kg
- ✓ ابعاد: ۲۳۲x۲۸۰ میلی متر



Models	AXIS Q6055-E 60 Hz AXIS Q6055-E 50 Hz	Storage: disruption, recording System: system ready Time: recurrence, use schedule Input signal: manual trigger, virtual input
Camera		
Image sensor	1/2.8" progressive scan CMOS	Event actions
Lens	4.44–142.6 mm, F1.6–4.41 Horizontal field of view: 62.8°–2.23° Vertical field of view: 36.8°–1.3° Autofocus, auto-iris	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP
Day and night	Automatically removable infrared-cut filter	Data streaming
Minimum illumination	Color: 0.3 lux at 30 IRE F1.6 B/W: 0.03 lux at 30 IRE F1.6 Color: 0.5 lux at 50 IRE F1.6 B/W: 0.04 lux at 50 IRE F1.6	Event data
Shutter time	1/33000 s to 1/3 s with 50 Hz 1/33000 s to 1/4 s with 60 Hz	Built-in installation aids
Pan/Tilt/Zoom	Pan: 360° endless, 0.05° – 450°/s Tilt: 220°, 0.05°–450°/s 32x optical zoom and 12x digital zoom, total 384x zoom E-flip, 256 preset positions, Tour recording, Guard tour, Control queue, On-screen directional indicator, Set new pan 0°, Adjustable zoom speed	Pixel counter
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	General
Resolution	HDTV 1080p 1920x1080 to 320x180 HDTV 720p 1280x720 to 320x180	Casing
Frame rate	Up to 50/60 fps (50/60 Hz) in HDTV 720p Up to 25/30 fps (50/60 Hz) in HDTV 1080p	IP66-, IP67-, NEMA 4X- and IK10-rated Metal casing (aluminum), polycarbonate (PC) clear dome, sunshield (PC/ASA)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology Controllable frame rate and bandwidth VBR/MBR H.264	Sustainability
Image settings	Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation	PVC free
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection	Memory
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, LLDP	512 MB RAM, 256 MB Flash
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org	Power
Analytics	Included AXIS Video Motion Detection, Autotracking, Active Gatekeeper, AXIS Fence Guard, AXIS Motion Guard Basic Analytics (not to be compared with third-party analytics): object removed, enter/exit detector, fence detector, object counter Highlight compensation Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Axis High PoE 60 W SFP midspan: 100–240 V AC, max 74 W Camera consumption: typical 16 W, max 60 W
Event triggers	Detectors: live stream accessed, video motion detection, shock detection Object removed, enter/exit detector, fence detector, object counter Hardware: fan, network, temperature, casing open PTZ: autotracking, error, moving, ready, preset reached	Connectors
		RJ45 10BASE-T/100BASE-TX PoE, RJ45 Push-pull Connector (IP66) included
		Storage
		Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
		Operating conditions
		With 30 W midspan: -20 °C to 50 °C (-4 °F to 122 °F) With 60 W midspan: -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing)
		Storage conditions
		-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals
		EMC EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1 IEC/EN/UL 60950-22 Environment EN 50121-4, IEC 62236-4, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, NEMA 250 Type 4X IEC/EN 60529 IP66 IEC 60721-4-3, IEC 60068-2-30, IEC 60068-2-60, IEC 60068-2-78, NEMA TS-2-2003 v02.06, Subsection 2.2.7, 2.2.8, 2.2.9; IEC 62262 IK10, ISO 4892-2 Network NIST SP500-267 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR
		Weight
		3.7 kg (8.2 lb)
		Dimensions
		Ø232 x 280 mm (Ø9 1/8 x 11 in)
		Included accessories
		Axis High PoE 60 W SFP midspan, RJ45 Push-pull Connector (IP66), Sunshield Installation Guide, Windows decoder 1-user license
		Optional accessories
		Smoked dome cover AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack
		Video management software
		AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
		Languages
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty
		Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty

