



دستگاه ایکس ری X-Ray

X6040

درباره ما

شرکت مهندسی مکسا مفتخر است که توانسته است طیف وسیعی از محصولات سخت افزاری مرتبط با حوزه امنیت کنترل تردد مانند انواع دوربین های مدار بسته، انواع دستگاه های حضور و غیاب، گیت های کنترل تردد، راهبندها، گیت ها و راکت های بازرسی بدنی و همچنین محصولات نرم افزاری شامل نرم افزار اکسس کنترل، نرم افزار جامع حراست، نرم افزار پلاک خوان و ... را در اختیار کلیه کسب و کارهای بزرگ ایرانی قرار دهد.

چرا مکسا را انتخاب کنیم؟

- ✓ ۵ سال گارانتی محصولات
- ✓ ۵ سال وارانتی محصولات
- ✓ پشتیبانی فعال
- ✓ کارشناس حضوری
- ✓ تعمیر دوره ای
- ✓ تعویض دستگاه
- ✓ نصب تخصصی
- ✓ تیکت پشتیبانی

مشخصات

- ✓ ابعاد تونل: ۴۰۰*۶۰۰ میلی متر
- ✓ سرعت نوار نقاله: ۰/۳ میلی ثانیه
- ✓ حداکثر بار: ۱۸۰ کیلوگرم
- ✓ ارتفاع نوار نقاله: ۶۸۰ میلی متر
- ✓ مانیتور ۲۱ اینچ LED
- ✓ استاندارد ASA / ISO ۱۶۰۰
- ✓ رابط: RJ45 (TCP/IP)
- ✓ ابعاد دستگاه: ۱۳۰۵*۹۱۰*۱۷۰۱ میلی متر
- ✓ پشتیبانی از نرم افزار ZKBio SIS
- ✓ ابعاد جعبه (پکیج): ۱۴۰۰*۱۱۵۰*۲۰۷ میلی متر
- ✓ وزن: ۳۸۰ کیلوگرم
- ✓ حداکثر ظرفیت ذخیره سازی ۲۰۰۰۰۰ تصویر اسکن شده



Technical Characteristics

Tunnel Dimensions (W*H)	600*400 (mm)
Conveyor Speed	0.3m/sec
Load on Conveyor	180kg (evenly distributed)
Conveyor Height	680 mm
Space Definition	Horizontal Φ 1.0mm Vertical Φ 2.0mm
Steel Penetration	35mm
Wire Resolution	38AWG
Dual-energy Detector	Yes
Number of Colors in X-ray Image	3
Dimensions (L*W*H)	1701*910*1305 (mm)
Package Dimensions (L*W*H)	2070*1150*1400 (mm)
Weight	380 kg
Package Weight	480 kg
Film Safety	ASA/ISO1600 standard of film safety
Single Inspection Dosage Rate	$\leq 1.0\mu\text{Gy}$
Supported Software	ZKBio SIS
Communication Interface	RJ45(TCP/IP)
Radiation Leak Dosage	$0.1\mu\text{Gy/h}$ (5cm from the surface)

Operating Environment

Operating Temperature	-10°C to +45°C
Storage Temperature	-20°C to +60°C
Humidity	5-95%, non-condensing
Power Supply	230 VAC +/- 10% / 60/50 Hz (EU) 110 VAC +/- 10% / 60/50 Hz (US)
Power Consumption	Max. 1.0 kVA
Sound Pressure	54dB

Computer Specifications

Processor	Intel® Braswell SoC N3160 (QC-2.24GHz)
Monitor	21" LED color
Memory	Onboard 4 GB RAM
Hard Drive	2TB
USB Port	4 ports
Max. Storage	Up to 200,000 scanned images

X-ray Generator

Tube Current	0.8 mA
Anode Voltage	150 kV rated
Generator Cool	Seal oil cooling / 100%
Orientation	Vertically upwards

Dimensions(mm)

