

KIOXIA CD9P-V Series (2.5-inch)

(KCD9XPUG/KCD9DPUG)

Data Center NVMe™ Mixed Use SSD

KIOXIA CD9P-V Series is a mixed use data center NVMe™ SSD that is optimized to support a broad range of scale-out and cloud applications. Built with a PCIe® 5.0 (32 GT/s x4) interface, the CD9P-V Series SSDs deliver consistent performance up to 2,600K IOPS (random read) and 750K IOPS (random write).

CD9P-V 2.5-inch form factor SSDs deliver 3 DWPD (Drive Writes Per Day) of endurance, making them well-suited for hyperscale data center applications, featuring KIOXIA BiCS FLASH™ 3D TLC flash memory generation 5 (for 1.6 TB and 3.2 TB models) and generation 8 (for 6.4 TB and 12.8 TB models).



Product image may represent a design model.

Key Features

- PCIe® 5.0, NVMe™ 2.0 specification compliant
- Open Compute Project Datacenter NVMe™ SSD specification v2.5 support (not all requirements)
- Form factor: 2.5-inch, 15 mm thickness
- Proprietary KIOXIA architecture: controller, firmware and BiCS FLASH™ 3D TLC flash memory generation 5 and generation 8
- Single-port design optimized for data center class workloads
- Consistent performance and reliability for demanding 24x7 environments
- Designed for high-density storage deployments
- Power Loss Protection (PLP) and End-to-End Data Protection
- Security options: SIE, SED^{[1][2][3][4]}

Key Applications

- Hyperscale
- IoT and big data analytics
- Online transaction processing (OLTP) (transactional and relational databases)
- Streaming media and content delivery networks
- Virtualized environments

Specifications

SIE Model Number	KCD9XPUG12T8	KCD9XPUG6T40	KCD9XPUG3T20	KCD9XPUG1T60
SED Model Number	KCD9DPUG12T8	KCD9DPUG6T40	KCD9DPUG3T20	KCD9DPUG1T60
Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB
Basic Specifications				
Form Factor	2.5-inch, 15mm thickness			
Interface	PCIe® 5.0, NVMe™ 2.0			
Maximum Interface Speed	128 GT/s (PCIe® Gen5 single x4)			
Flash Memory Type	BiCS FLASH™ TLC			



Specifications (Continued)

Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB
Performance (Up to)				
Sustained 128 KiB Sequential Read	14,800 MB/s		14,500 MB/s	
Sustained 128 KiB Sequential Write	7,000 MB/s			3,600 MB/s
Sustained 4 KiB Random Read	2,600K IOPS			2,000K IOPS
Sustained 4 KiB Random Write	750K IOPS		600K IOPS	310K IOPS
Power Requirements				
Supply Voltage	12 V ± 10 %, 3.3 V ± 15 %			
Power Consumption (Active)	23W typ.			
Power Consumption (Ready)	5W typ.			
Reliability				
MTTF	2,500,000 hours			
Warranty	5 years			
DWPD	3			
Dimensions				
Thickness	15 mm +0 / -0.5 mm			
Width	69.85 mm ± 0.25 mm			
Length	100.45 mm Max			
Weight	130 g Max			
Environmental				
Temperature (Operating)	0 °C to 75 °C			
Temperature (Non-operating)	-40 °C to 85 °C			
Humidity (Operating)	5 % to 95 % R.H.			
Vibration (Operating)	21.27 m/s² { 2.17 Grms } (5 to 800 Hz)			
Shock (Operating)	9.8 km/s² { 1,000 G } (0.5 ms)			

Definition of capacity: Kioxia Corporation defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1 GB = 2^30 = 1,073,741,824 bytes and 1TB = 2^40 bytes = 1,099,511,627,776 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

GT/s: Giga Transfers per second.

A kibibyte (KiB) means 2^10, or 1,024 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Writes Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day under the specified workload for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

Read and write speed may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

IOPS: Input Output Per Second (or the number of I/O operations per second).

Temperature (operating): Specified by the composite temperature reported by SMART.

[1] Sanitize Instant Erase (SIE) and Self-Encrypting Drive (SED) security optional models are available.

[2] SIE optional model supports Cryptographic Erase, which is a standardized feature defined by the technical committees (SCSI) of INCITS (the InterNational Committee for Information Technology Standards).

[3] SED optional model supports TCG Opal and Ruby SSCs. It has a few unsupported features of TCG Opal SSC. For more details, please make inquiries through “Contact us” in each region's website, <https://www.kioxia.com/>

[4] Security optional models are not available in all countries due to export and local regulations.

All information provided here is subject to change without prior notice.

PCIe is a registered trademark of PCI-SIG.

NVMe is a registered or unregistered mark of NVM Express, Inc. in the United States and other countries.

Other company names, product names, and service names may be trademarks of third-party companies.



KIOXIA CD9P-V Series (E3.S)

(KCD9XPJE/KCD9DPJE)

Data Center NVMe™ Mixed Use SSD

KIOXIA CD9P-V Series is a mixed use data center NVMe™ SSD that is optimized to support a broad range of scale-out and cloud applications. Built with a PCIe® 5.0 (32 GT/s x4) interface, the CD9P-V Series SSDs deliver consistent performance up to 2,600K IOPS (random read) and 750K IOPS (random write).

CD9P-V E3.S form factor SSDs deliver 3 DWPD (Drive Writes Per Day) of endurance, making them well-suited for hyperscale data center applications, featuring KIOXIA BiCS FLASH™ 3D TLC flash memory generation 5 (for 1.6 TB and 3.2 TB models) and generation 8 (for 6.4 TB and 12.8TB models).



Product image may represent a design model.

Key Features

- PCIe® 5.0, NVMe™ 2.0 specification compliant
- Open Compute Project Datacenter NVMe™ SSD specification v2.5 support (not all requirements)
- Form factor: E3.S, 7.5 mm thickness
- Proprietary KIOXIA architecture: controller, firmware and BiCS FLASH™ 3D TLC flash memory generation 5 and generation 8
- Single-port design optimized for data center class workloads
- Consistent performance and reliability for demanding 24x7 environments
- Designed for high-density storage deployments
- Power Loss Protection (PLP) and End-to-End Data Protection
- Security options: SIE, SED^{[1][2][3][4]}

Key Applications

- Hyperscale
- IoT and big data analytics
- Online transaction processing (OLTP) (transactional and relational databases)
- Streaming media and content delivery networks
- Virtualized environments

Specifications

SIE Model Number	KCD9XPJE12T8	KCD9XPJE6T40	KCD9XPJE3T20	KCD9XPJE1T60
SED Model Number	KCD9DPJE12T8	KCD9DPJE6T40	KCD9DPJE3T20	KCD9DPJE1T60
Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB
Basic Specifications				
Form Factor	E3.S			
Interface	PCIe® 5.0, NVMe™ 2.0			
Maximum Interface Speed	128 GT/s (PCIe® Gen5 single x4, dual x2)			
Flash Memory Type	BiCS FLASH™ TLC			



Specifications (Continued)

Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB
Performance (Up to)				
Sustained 128 KiB Sequential Read	14,800 MB/s		14,500 MB/s	
Sustained 128 KiB Sequential Write	7,000 MB/s			3,600 MB/s
Sustained 4 KiB Random Read	2,600K IOPS			2,000K IOPS
Sustained 4 KiB Random Write	750K IOPS		600K IOPS	310K IOPS
Power Requirements				
Supply Voltage	12 V ± 10 %, 3.3 V ± 15 %			
Power Consumption (Active)	23W typ.			
Power Consumption (Ready)	5W typ.			
Reliability				
MTTF	2,500,000 hours			
Warranty	5 years			
DWPD	3			
Dimensions				
Thickness	7.5 mm +0.2 / -0.5 mm			
Width	76 mm ± 0.25 mm			
Length	112.75 mm ± 0.4 mm			
Weight	110 g Max			
Environmental				
Temperature (Operating)	0 °C to 75 °C			
Temperature (Non-operating)	-40 °C to 85 °C			
Humidity (Operating)	5 % to 95 % R.H.			
Vibration (Operating)	21.27 m/s² { 2.17 Grms } (5 to 800 Hz)			
Shock (Operating)	9.8 km/s² { 1,000 G } (0.5 ms)			

Definition of capacity: Kioxia Corporation defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1 GB = 2³⁰ = 1,073,741,824 bytes and 1TB = 2⁴⁰ bytes = 1,099,511,627,776 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

GT/s: Giga Transfers per second.

A kibibyte (KiB) means 2¹⁰, or 1,024 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Writes Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day under the specified workload for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

Read and write speed may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

IOPS: Input Output Per Second (or the number of I/O operations per second).

Temperature (operating): Specified by the composite temperature reported by SMART.

[1] Sanitize Instant Erase (SIE) and Self-Encrypting Drive (SED) security optional models are available.

[2] SIE optional model supports Cryptographic Erase, which is a standardized feature defined by the technical committees (SCSI) of INCITS (the InterNational Committee for Information Technology Standards).

[3] SED optional model supports TCG Opal and Ruby SSCs. It has a few unsupported features of TCG Opal SSC. For more details, please make inquiries through "Contact us" in each region's website, <https://www.kioxia.com/>

[4] Security optional models are not available in all countries due to export and local regulations.

All information provided here is subject to change without prior notice.

PCIe is a registered trademark of PCI-SIG.

NVMe is a registered or unregistered mark of NVM Express, Inc. in the United States and other countries.

Other company names, product names, and service names may be trademarks of third-party companies.

